

AMENDED CLAIMS

1.(Cancelled)

2.(Cancelled)

3.(Cancelled)

4.(Previously Presented) A method for selecting and feeding articles to blister packs or containers, from a main hopper, filled with articles, the method comprising:

providing an auxiliary hopper filled with unselected articles;

providing selecting means for allowing free passage of size-matching articles or of articles smaller than a nominal size of said size-matching articles for feeding said main hopper, while stopping size-non-matching articles whose dimensions are bigger than said nominal size,

feeding said main hopper with articles allowed free passage by said selecting means from said auxiliary hopper,

passing size-matching articles through the selecting means and stopping size-non-matching articles within tubular portions of said selecting means and swinging the tubular portions downwardly to remove the size non matching articles to maintain a regular article feeding flow;

feeding said blister packs or containers with the size-matching articles contained in said main hopper, wherein the size-non-matching articles passing through the selecting means are stopped due to interception performed by the tubular portions of said selecting means having an inner section matching the nominal size of the articles, so as to stop such size-non-matching articles.

5.(Cancelled)

6.(Currently Amended) A method, according to claim ~~4~~ 4, further including checking presence of articles forming a flow of articles through first channels connected to said selecting means, and operating said selecting means upon detection of the flow having being interrupted, to remove size-non-matching articles and restore said flow of size-matching articles through said first channels.

7.(Currently Amended) A method, according to claim ~~4~~ 4, further including cyclical operation of said selecting means to remove size-non-matching articles possibly stopped within or by said selecting means, to keep a continuous flow of size-matching articles.

8.(Currently Amended) A method, according to claim ~~4~~ 4, wherein said selecting means are fed with an article flow rate higher than the flow rate of size-matching articles fed to said blisters or containers, so as to allow said size-matching articles to accumulate in said main hopper and a continuous feeding of articles to the blisters or containers.

9.(Currently Amended) A method according to claim ~~4~~ 4, characterized in that the articles removed from said selecting means are collected in a collecting container to be sorted and recycled.

10.(Cancelled)

11.(Currently Amended) An apparatus, according to claim ~~10~~ 18, further including sensor means, situated along said selecting means for detecting possible interruption of a flow of articles and for operating said selecting means, so as to remove size-non-matching articles

stopped within said selecting means or by said selecting means.

12.(Currently Amended) An apparatus, according to claim ~~10~~ 18, wherein said selecting means are operated cyclically to remove size-non-matching articles possibly stopped within said selecting means or by said selecting means, and to restore a continuous flow of size-matching articles.

13.(Cancelled)

14.(Currently Amended) An apparatus, according to claim ~~13~~ 22, further including ~~includes~~ sensor means, situated downstream of said selecting means for detecting the continuity of flow of articles into said first channel and for operating said selecting means, so as to remove size-non-matching articles stopped within said selecting means or by said selecting means.

15.(Currently Amended) An apparatus according to claim ~~10~~ 18, including a chute connected to said selecting means and leading to said main hopper.

16.(Original) An apparatus, according to claim 15, wherein said selecting means are operated cyclically to remove size-non-matching articles possibly stopped within said selecting means or by said selecting means, and to restore a continuous flow of size-matching articles.

17.(Currently Amended) An apparatus, according to claim ~~10~~ 18, further including a first linear vibrating conveyor situated downstream of said auxiliary hopper, for feeding unselected articles to a selector, which is substantially inclined and leads to said selecting means.

18.(Previously Presented) An apparatus for selecting and feeding articles to blister packs or containers, from a main hopper filled with articles, the apparatus comprising:

an auxiliary hopper, containing unselected articles for feeding said main hopper; and

selecting means, situated between said auxiliary hopper and said main hopper, having an inlet side, to receive said unselected articles, and an outlet side, to exit selected articles, said selecting means being provided with a cross section matching a nominal size of selected articles to provide size-matching articles which are fed to said main hopper, the selecting means allowing free passage of the size-matching articles or of articles smaller than said nominal size, and stopping for removal size-non-matching articles, so that said main hopper contains only size-matching articles for feeding said blister packs or containers, said selecting means including at least one tubular portion having an inlet side and an outlet side, having internal dimension matching the nominal size of said articles, said tubular portion moving from one normal operation configuration, in which in which a flow of articles is allowed to pass, to a discharge configuration, in which the tubular portion is rotated to discharge size-non-matching articles jammed and stopped within said tubular portion or against said inlet side of said tubular portion, and further including ejecting means for interacting with said tubular portion, when in the discharge configuration, from the outlet side, so as to remove the articles present therein or stopped by said inlet side.

19.(Cancelled).

20.(Original) An apparatus, according to claim 18, further including first brush type rotating means, connected to and situated above said tubular portions for drawing back, with respect to the forward movement direction, unselected articles not correctly oriented with respect to said tubular portions during normal feeding of the articles, thus maintaining a single feeding layer of the articles introduced into said tubular portion.

21.(Original) An apparatus, according to claim 20, wherein, when the tubular portions are set in their discharge configuration, said first brush type rotating means refrain said unselected articles from continuing their motion and being removed.

22.(Currently Amended) An apparatus for selecting and feeding articles to blister packs or containers, from a main hopper filled with articles, the apparatus comprising:

an auxiliary hopper, containing unselected articles for feeding said main hopper; and selecting means, situated between said auxiliary hopper and said main hopper, having an inlet side, to receive said unselected articles, and an outlet side, to exit selected articles, said selecting means being provided with a cross section matching a nominal size of selected articles to provide size-matching articles which are fed to said main hopper, the selecting means allowing free passage of the size-matching articles or of articles smaller than said nominal size, and stopping for removal size-non-matching articles, so that said main hopper contains only size-matching articles for feeding said blister packs or containers;

at least one first channel connected to said selecting means and leading to said main hopper, said selecting means include a tapered inlet section for each first channel and a shutter connected to said tapered inlet section, said shutter opened to discharge jammed and stopped articles;

a first linear vibrating conveyor situated downstream of said auxiliary hopper, for feeding unselected articles to a selector, which is substantially inclined and leads to said selecting means; and, Apparatus, according to claim 17, further including a second substantially horizontal linear vibrating conveyor situated downstream of said main hopper for feeding size-matching articles to a loader leading to said blisters or containers.

23.(Original) An apparatus, according to claim 22, further including second brush type rotating means connected to and situated above said loader, for drawing back, with respect to

the movement forward direction, the size-matching articles not correctly oriented, thus maintaining a single feeding layer of size-matching articles fed to said blister packs or containers.

24.(Previously Presented) An apparatus, according to claim 18, wherein said ejecting means are operated by pneumatic cylinders.

25.(Cancelled)

26.(Currently Amended) An apparatus, according to claim ~~13~~ 22, further including a plurality of second channels, substantially parallel and arranged one beside another, fed by said main hopper, for feeding size matching articles to said blisters or containers.

27.(Currently Amended) An apparatus, according to claim ~~13~~ 22, including a plurality of first channels, substantially parallel and arranged one beside another, fed by said auxiliary hopper and leading to said main hopper, and a plurality of second channels, substantially parallel and arranged one beside another, fed by said main hopper, for feeding size matching articles to said blisters or containers.

28.(Currently Amended) An apparatus, according to claim ~~10~~ 18, wherein the flow rate of unselected articles fed to said selecting means is higher than the flow rate of size-matching articles fed to said blisters or containers, so as to allow said size-matching articles to accumulate inside said main hopper.

29.(Currently Amended) An apparatus, according to claim ~~10~~ 18, wherein when the selecting

means are operated, the discharged articles are sent to a collecting container.